



Photo et textes non contractuels

## Product Information:

45° tilting head to the left and the right  
Rapid clamping vice.  
Burr-free double vice  
Mobile jaw to perform right 45° cut  
Protective cover of detachable saw mill  
Lubrication system of saw mill using a pump  
Drive through an oil-bath reducer  
Steel cast iron frame  
Control arm fitted with a trigger switch  
Very low voltage controls 24 V  
Emergency Stop through a mushroom stay put button  
Electronic speed variator  
Electrical insulation IP 54

### Supplie with:

- base
- Circular saw blade
- 540 mm adjustable cut stop

## TS 315V

(Ref. 20114202)

Cutting under lubrication of steel, stainless steel and aluminum

**Usage régulier**

Guarantee:  

## Technical characteristics:

Height (cm) : 183.00  
Width (cm) : 99.00  
Length (cm) : 102.00  
Net weight (Kg) : 178.00  
Power(kW) 1.5  
Power (V) 3-phases 400V  
Rotation speed (rpm) 15-120  
Round cutting capacity (mm) at 90° 100  
Square cutting capacity (mm) at 90° 82  
Rectangle cutting capacity (mm) at 90° 110 x 70  
Left round cutting capacity (mm) at 45° 90  
Left square cutting capacity (mm) at 45° 80  
Left rectangle cutting capacity (mm) at 45° 85 x 70  
Vice opening (mm) 120  
Working height (mm) 970  
Dimension of the blade 315 x 2.5 x 32  
Right rectangle cutting capacity (mm) at 45° 85 x 70  
Right round cutting capacity (mm) at 45° 90  
Left square cutting capacity (mm) at 45° 80  
Abrasive disc dimension (mm) 315 x 2.5 x 32