

tank



Photo et textes non contractuels

JET 15 i

(Ref. 20402040)

Water and dust suction

Usage intensif spécifique

Norm: EN 60335-2-69

Guarantee:  

Product Information:

Manual unclogging system of the filter using a single button

Water-resistant high-efficiency 9.9% Class M cartridge filter

Metal accessories and stainless steel tubes

Carbon-fibre reinforced base

Storage unit of accessories integrated to the base

Large 2-wheel + 2 castors for a stabilised stability

Anti-crushing shielded hose

By-

pass cooling down system 1450W motor designed for continuous heavy-duty jobs (air is sucked by a third turbine on top of the motor, only for cooling down)

Suction, depression and cutting-off high-performance

Anti-static electricity plate connected to earth

Neoprene power table HO7 RNF length 7 m

Standard accessories:

- Bent tubes 2 x 500 mm Ø 32 mm
- hose Ø 32 mm, length 2,2 m
- liquid nozzle de 400 mm
- dual-purpose nozzle - 270 mm
- round brush
- flat nozzle
- Padding nozzle
- Class M cartridge filter PTFE

Technical characteristics:

Height (cm) : 60.00

Width (cm) : 46.00

Length (cm) : 43.00

Net weight (Kg) : 10.00

Power (W) 1450

Power (V) 1-phase 230V

Tank stainless steel

Tank capacity (l) 20

Depression (Kpa) 26.7

Flow (l/min) 4 200

Sound level (dBA) 74

Atex Zone 22 No

Accessory diameter (mm) 32

Unclogging Yes

Class-M approved No

Vacuum cleaner filter Class M PET cartridge

Synchro socket No

Cable length (m) 7

Tank capacity (L) 23