

tank



Photo et textes non contractuels

JET 30 i

(Ref. 20402041)

Water and dust
suction

Usage très intensif

Norm: EN 60335-2-69

Guarantee:  

Product Information:

"Manual unclogging system of the filter using a single button

Water-resistant high-efficiency 9.9% Class M cartridge filter

Metal accessories and stainless steel tubes

Carbon-fibre reinforced base

Storage unit of accessories integrated to the base

Large reinforced 2-wheel + 2-caster base for an optimised stability

Anti-crushing shielded hose

By-

pass cooling down system 1450W motor designed for continuous heavy-duty jobs (air is sucked by a third turbine on top of the motor, only for cooling down)

Suction, depression and cutting-off high-performance Anti-static electricity plate connected to earth

Neoprene power table HO7 RNF length 7 m"

Standard accessories:

- Bent tubes 2 x 500 mm Ø 40 mm
- hose Ø 40 mm, length 2.5 m
- Dust nozzle - 400 mm
- liquid nozzle - 400 mm
- round brush
- flat nozzle
- round brush fitting
- Class M cartridge filter PTFE

Technical characteristics:

Height (cm) : 80.00

Width (cm) : 53.00

Length (cm) : 43.50

Net weight (Kg) : 11.60

Power (W) 1450

Power (V) 1-phase 230V

Tank stainless steel

Tank capacity (l) 35

Depression (Kpa) 26.7

Flow (l/min) 4200

Sound level (dBA) 74

Atex Zone 22 No

Accessory diameter (mm) 40

Unclogging Yes

Class-M approved No

Vacuum cleaner filter Class M PET cartridge

Synchro socket No

Cable length (m) 7

Tank capacity (L) 38