

tank



Photo et textes non contractuels

Product Information:

"Manual unclogging system of the filter using a single button
Water-resistant high-efficiency 9.9% Class M cartridge filter
Metal accessories and stainless steel tubes
Storage unit of accessories integrated to the trolley
Large reinforced 2-wheel + 2-caster trolley for an optimised stability
Swivelling tank making easier liquid emptying
Anti-crushing shielded hose
Dual-turbine suction
By-pass cooling down system motor designed for heavy-duty jobs (air is sucked by a third turbine on top of the motor, only for cooling down)
Anti-static electricity plate connected to earth
Separate switch per motor
Neoprene power table HO7 RNF length 7 m"

"Standard accessories:

- Bent tubes 2 x 500 mm Ø 40 mm
- hose Ø 40 mm, length 2.5 m
- Dust nozzle - 400 mm
- liquid nozzle - 400 mm
- round brush
- flat nozzle
- round brush fitting
- Class M cartridge filter PTFE

JET 60 P

(Ref. 20402047)

Water and dust suction

Usage très intensif

Norm: EN 60335-2-69

Guarantee:  

Technical characteristics:

Height (cm) : 94.00
Width (cm) : 65.00
Length (cm) : 51.00
Net weight (Kg) : 27.40
Power (W) 2 x 1200
Power (V) 1-phase 230V
Tank Polypropylene
Tank capacity (l) 50
Depression (Kpa) 23.52
Flow (l/min) 7 070
Sound level (dBA) 76.5
Atex Zone 22 No
Accessory diameter (mm) 40
Unclogging Yes
Class-M approved No
Vacuum cleaner filter Class M PET cartridge
Synchro socket No
Cable length (m) 7
Tank capacity (L) 78