

tank



Photo et textes non contractuels

JET 100P

(Ref. 20402048)

Water and dust
suction

Usage très intensif

Norm: EN 60335-2-69

Guarantee:  

Product Information:

"Manual unclogging system of the filter using a single button

Water-resistant high-efficiency 9.9% Class M cartridge filter

Metal accessories and stainless steel tubes

Storage unit of accessories integrated to the trolley

Large reinforced 2-wheel + 2-caster trolley for an optimised stability

Swivelling tank making easier liquid emptying

Anti-crushing shielded hose

Dual-turbine suction

By-pass cooling down system motor designed for heavy-duty jobs (air is sucked by a third turbine on top of the motor, only for cooling down)

Anti-static electricity plate connected to earth

Separate switch per motor

Neoprene power table HO7 RNF length 7 m"

"Standard accessories:

- Bent tubes 2 x 500 mm Ø 40 mm
- hose Ø 40 mm, length 2.5 m
- Dust nozzle - 400 mm
- liquid nozzle - 400 mm
- round brush
- flat nozzle
- round brush fitting
- Class M cartridge filter PTFE

Technical characteristics:

Height (cm) : 101.00

Width (cm) : 64.00

Length (cm) : 51.50

Net weight (Kg) : 30.40

Power (W) 3 x 1200

Power (V) 1-phase 230V

Tank Polypropylene

Tank capacity (l) 55

Depression (Kpa) 25.5

Flow (l/min) 10 600

Sound level (dBA) 78

Atex Zone 22 No

Accessory diameter (mm) 40

Unclogging Yes

Class-M approved No

Vacuum cleaner filter Class M PET cartridge

Synchro socket No

Cable length (m) 7

Tank capacity (L) 88