

Stainless steel tank



Photo et textes non contractuels

## JET 30 i DR

(Ref. 20402052)

Water, dust, soot and ash aspiration

**Usage très intensif**

Norm: EN 60335-2-69

Guarantee:  

### Product Information:

"Manual unclogging system of the filter using a single button  
special class M cartridge filter for fuel soot  
Anti-clogging nylon over filter  
Metal accessories and stainless steel tubes  
Carbon-fibre reinforced base  
Storage unit of accessories integrated to the base  
Large reinforced 2-wheel + 2-castor base for an optimised stability  
Anti-crushing shielded hose  
By-pass cooling down system 1450W motor designed for continuous heavy-duty jobs (air is sucked by a third turbine on top of the motor, only for cooling down)  
Suction, depression and cutting-off high-performance  
Anti-static electricity plate connected to earth  
Neoprene power table HO7 RNF length 7 m"

### Standard accessories:

- Bent tubes 2 x 500 mm Ø 40 mm
- hose Ø 40 mm, length 5 m
- Dust nozzle - 400 mm
- flat nozzle inox 600 mm
- Class H cartridge filter PTFE

### Technical characteristics:

Height (cm) : 80.00  
Width (cm) : 53.00  
Length (cm) : 43.50  
Net weight (Kg) : 11.60  
Power (W) 1450  
Power (V) 1-phase 230V  
Tank stainless steel  
Tank capacity (l) 35  
Depression (Kpa) 26.7  
Flow (l/min) 4 200  
Sound level (dBA) 74  
Atex Zone 22 No  
Accessory diameter (mm) 40  
Unclogging Yes  
Class-M approved No  
Vacuum cleaner filter Class H cartridge  
Synchro socket No  
Cable length (m) 7  
Tank capacity (L) 38