

tank



Photo et textes non contractuels

MC 55 i

(Ref. 20403006)

Water and dust
suction

Usage régulier

Norm: EN 60335-2-69

Guarantee:  

Product Information:

"Fitted standard with a class L filter
Anti-crushing shielded hose
4-wheel stand for optimised motion
Dual turbine suction

By-

pass cooling motor (air is sucked up by a third turbine on top of the
motor, only for cooling down). Designed for heavy-duty jobs

Vinyl power cable H05 VV-F length 7 m

Separate switch per motor

Standard accessories:

- plastic tubes
- liquid nozzle
- suceur à poussières
- round brush
- flat nozzle
- hose, length 2,7 m Ø 40 mm

Technical characteristics:

Height (cm) : 92.50
Width (cm) : 52.00
Length (cm) : 52.00
Net weight (Kg) : 23.00
Repairability index 8,8/10
Power (W) 2 x 1000
Power (V) 1-phase 230V
Tank stainless steel
Tank capacity (l) 50
Depression (Kpa) 22.54
Flow (l/min) 7 080
Sound level (dBA) 84
Atex Zone 22 No
Accessory diameter (mm) 40
Unclogging No
Class-M approved No
Vacuum cleaner filter Class L
Synchro socket No
Cable length (m) 7
Tank capacity (L) 78