



## PE 22A

(Ref. 20502055)

Dry drilling of metals, plastic materials and wood  
(lubrification en option)

**Usage régulier**

Guarantee:  

Photo et textes non contractuels

### Product Information:

Steel cast iron column  
Transmission through steel dented belt and wheels  
Spindle fitted on bearings  
ON/OFF switch fitted with a lack of voltage coil  
Emergency Stop through mushroom stay put button  
Protective shield of servo chuck  
Tilting square table up to 45°, with liquid collector  
Rack-driven table  
Digital readout of the drilling depth  
Digital display of the spindle speed  
Drilling-position laser  
LED lighting  
Pulley cover fitted with a grip-safety microswitch

#### Supplied with:

- Self-clamping chuck 16 mm
- Chuck shank
- Taper drift

### Technical characteristics:

Height (cm) : 98.00  
Width (cm) : 43.00  
Length (cm) : 66.00  
Net weight (Kg) : 49.00  
Power(kW) 0.55  
Power (V) 1-phase 230V  
Spindle speed (rpm) 210 - 2880  
Max. drilling capacity (mm) 22  
Morse taper MT2  
Column dia (mm) 72  
Spindle stroke (mm) 85  
Number of gears 16  
d: spindle/column distance (mm) 160  
e: spindle/base distance (mm) 630  
f: spindle/table distance (mm) 440  
Table dimension (mm) 286 x 286  
Lighting Yes  
Servo screen Yes  
Reversible vice table No  
Coolant No  
Automatic down motion (mm/tr) No  
Slow down motion No  
Semi automatic tapping No  
Cross motion table No