



Photo et textes non contractuels

25 FV

(Ref. 20502080)

Drilling, tapping, milling metals, plastic materials and wood,
(coolant is optional)

Usage intensif

Guarantee:  

Product Information:

Steel cast iron frame, head and stand
Dovetail column
Emergency Stop through mushroom stay put button
Semi automatic tapping system on handles and instant return
Left and right tilting milling head
Slow down motion
Servo polycarbonate screen
Cross-motion table, stroke 145 x 400 mm
Table grooving - distance between centers 45 mm
Electronic speed variator
Digital display of the spindle speed et de la profondeur de perçage

Supplied with:

- Self-clamping chuck 16 mm
- Chuck shank
- rapid-clamping vice 100 mm
- Without stand

Technical characteristics:

Height (cm) : 99.00
Width (cm) : 72.00
Length (cm) : 76.00
Net weight (Kg) : 165.00
Power(kW) 1
Power (V) 1-phase 230V
Spindle speed (rpm) 100 : 1800
Max. drilling capacity (mm) 25
Max. tapping capacity (mm) M12
Milling capacity (mm) 50
Morse taper MT3
Spindle stroke (mm) 70
Number of gears Variable
d: spindle/column distance (mm) 235
f: spindle/table distance (mm) 380
Table dimension (mm) 550 x 160
Distance between table grooves (mm) 45
Lighting No
Servo screen Yes
Reversible vice table No
Coolant No
Transversal / longitudinal stroke (mm) 145 x 400
Automatic down motion (mm/tr) No
Slow down motion Yes
Semi automatic tapping Yes
Cross motion table Yes