



SPC 32 TC VEL DL T

(Ref. 20601146)

Drilling metals, plastic materials and wood, with coolant

Usage très intensif

Guarantee:  

Photo et textes non contractuels

Product Information:

Cross move table
Electronic speed variator
Slow down motion
Semi automatic tapping
Steel cast iron frame, head and stand
Steel column
Machined aluminium pulleys
Transmission through V belts with rapid adjustment of tension
Spindle fitted on bearings
Adjustable spindle rack motion through return spring
24V very low voltage controls :
- ON/OFF
- Switching on lamp
- Emergency Stop through mushroom stop button
- 3-point locking circuit breaker
Detachable servo protective shield
24V lighting
Electrical protection IP54

Technical characteristics:

Height (cm) : 180.00
Width (cm) : 43.50
Length (cm) : 88.00
Net weight (Kg) : 350.00
Power(kW) 1.5
Power (V) 3-phase 400V
Spindle speed (rpm) 80 - 2030
Max. drilling capacity (mm) 32
Milling capacity (mm) 60
Morse taper MT3
Column dia (mm) 110
Spindle stroke (mm) 110
Number of gears 14
d: spindle/column distance (mm) 280
e: spindle/base distance (mm) 1 210
f: spindle/table distance (mm) 50-630
Table dimension (mm) 240 x 600
Distance between table grooves (mm) 130
Lighting Yes
Servo Screen Yes
Reversible vice table No

Noise level 50 dB

Rack-driven table, graisseur de la vis sans fin

Hot weather adaptation on request

Can be modified to 230V three-phase on request

Machined aluminium pulleys

Coolant Yes

Transversal / longitudinal stroke (mm) 265 x 480

Automatic down motion (mm/tr) No

Slow down motion Yes

Semi automatic tapping Yes

Cross motion table Yes

Supplied with Self-clamping chuck and Chuck shank