



## EXPERT 22 PEV tri

(Ref. 20502087)

Dry drilling of metals, plastic materials and wood  
(lubrification en option)

**Usage régulier**

Guarantee:  

Photo et textes non contractuels

### Product Information:

Mechanical variable speed drive with belts  
Steel cast iron column  
Transmission through belt and steel wheels  
Spindle fitted on bearings  
ON/OFF switch fitted with a lack of voltage coil  
Emergency Stop through mushroom stay put button  
Protective shield of servo chuck  
Tilting square table up to 45°, with liquid collector  
Rack-driven table  
Digital readout of the drilling depth  
Digital display of the spindle speed  
Drilling-position laser  
LED lighting  
Pulley cover fitted with a grip-safety microswitch  
Changement des vitesses par volant à manipuler en fonctionnement

#### Supplied with:

- Self-clamping chuck 16 mm
- Chuck shank
- Taper drift

### Technical characteristics:

Height (cm) : 98.00  
Width (cm) : 43.00  
Length (cm) : 66.00  
Net weight (Kg) : 61.00  
Power(kW) 0.75  
Power (V) 3-phases 400V  
Spindle speed (rpm) 400 : 2000  
Max. drilling capacity (mm) 22  
Morse taper MT2  
Column dia (mm) 72  
Spindle stroke (mm) 80  
Number of gears Variable  
d: spindle/column distance (mm) 180  
e: spindle/base distance (mm) 600  
f: spindle/table distance (mm) 415  
Table dimension (mm) 305 x 305  
Distance between table grooves (mm) en croix  
Lighting Yes  
Servo screen Yes  
Reversible vice table No  
Coolant No  
Jaw width (mm) 125  
Jaw height (mm) 28  
Opening (mm) 115  
Automatic down motion (mm/tr) No  
Slow down motion No  
Semi automatic tapping No  
Cross motion table No