



## EXPERT 22 PE Mono

(Ref. 20502101)

Dry drilling of metals, plastic materials and wood (lubrification en option)

**Usage régulier**

Guarantee:  

Photo et textes non contractuels

### Product Information:

- Steel cast iron column
- Transmission through steel dented belt and wheels
- Spindle fitted on bearings
- ON/OFF switch fitted with a lack of voltage coil
- Emergency Stop through mushroom stay put button
- Protective shield of servo chuck
- Tilting square table up to 45°, with liquid collector
- Rack-driven table
- Digital readout of the drilling depth
- Digital display of the spindle speed
- Drilling-position laser
- LED lighting
- Pulley cover fitted with a grip-safety microswitch

### Supplied with :

- Self-clamping chuck 16 mm
- Chuck shank
- Taper drift
- Screw vice and set of clamps

### Technical characteristics:

- Height (cm) : 98.00
- Width (cm) : 43.00
- Length (cm) : 66.00
- Net weight (Kg) : 61.00
- Power(kW) 0.75
- Power (V) 1-phase 230V
- Spindle speed (rpm) 210 - 2880
- Max. drilling capacity (mm) 22
- Morse taper MT2
- Column dia (mm) 72
- Spindle stroke (mm) 85
- Number of gears 16
- d: spindle/column distance (mm) 180
- e: spindle/base distance (mm) 600
- f: spindle/table distance (mm) 415
- Table dimension (mm) 305 x 305
- Lighting Yes
- Servo screen Yes
- Reversible vice table No
- Coolant No
- Automatic down motion (mm/tr) No
- Slow down motion No
- Semi automatic tapping No
- Cross motion table No