



EXPERT 30 PCTE

(Ref. 20502106)

Dry drilling of metals, plastic materials and wood
(lubrification en option)

Usage Général

Guarantee:  

Photo et textes non contractuels

Product Information:

Steel cast iron column
Transmission through steel dented belt and wheels
Spindle fitted on bearings
ON/OFF switch fitted with a lack of voltage coil
Emergency Stop through mushroom stay put button
Protective shield of servo chuck
Reversible tilting vice table up to 45°, with coolant collector
Rack-driven table Digital readout of the drilling depth
Digital display of the spindle speed
Drilling-position laser
LED lighting
Pulley cover fitted with a grip-safety microswitch
Vice on guideways, 200-mm jaws, 165-mm opening

Supplied with:

- Self-clamping chuck 16 mm
- Chuck Shank
- Taper drift

Technical characteristics:

Height (cm) : 172.00
Width (cm) : 47.00
Length (cm) : 77.50
Net weight (Kg) : 140.00
Power(kW) 1.1
Power (V) 3-phase 400V
Spindle speed (rpm) 150 - 2450
Max. drilling capacity (mm) 30
Morse taper MT3
Column dia (mm) 92
Spindle stroke (mm) 120
Number of gears 12
d: spindle/column distance (mm) 250
e: spindle/base distance (mm) 1 215
f: spindle/table distance (mm) 755
Table dimension (mm) 470 x 420
Distance between table grooves (mm) 2 x 122
Lighting Yes
Servo screen Yes
Reversible vice table Yes
Coolant No
Jaw width (mm) 208
Jaw height (mm) 53
Opening (mm) 165
Automatic down motion (mm/tr) No
Slow down motion No
Semi automatic tapping No
Cross motion table No