

tank



Photo et textes non contractuels

ULTRA ASP 40P-H

(Ref. 20405050)

Suction of water, dust, and wood
dust**Usage intensif spécifique**

Norm: EN 60335-2-69, Classe H

Guarantee:  

Product Information:

"Class M approved vacuum cleaner No-bag water and fine or clogging fine dust suction Automatic unclogging system, the filter is automatically unclogged through air pulse s, during a 2.2 s cycle every 15 s, without any suction interruption Unpluggable unclogging system Fitted with an electrical socket to perform a synchronised start using an electroportable tool 100 to 2 400 W Main PTFE filter: low dust adhesion, rot-proof and washable Pre-fitted with adaptors for storage box support, Sortimo or Systainer (optional) Accessory support Support hose Power cable support Elastic strap to hold the tools Anti-crushing shielded hose fitted with 2 wheels + 2 brake-swivelling metal castors Tank handle Smooth motor start through electronic speed variator Motor overheat safety device with automatic switching off Neoprene power table H05 RR-F 3G 1,5 length 7,5 m Antistatic"

Standard accessories:

- Bent stainless steel tube 400 mm
- Straight stainless steel tubes 2 x 500 mm
- hose Ø 36 mm, length 4 m
- water and dust nozzle 400 mm
- flat nozzle 200 mm
- Class M PTFE flat main filter
- plastic bag
- sac plastique d'évacuation

Technical characteristics:

Height (cm) : 60.50
Width (cm) : 38.50
Length (cm) : 56.50
Net weight (Kg) : 16.00
Power (W) 1400
Power (V) 1-phase 230V
Tank Polypropylene
Tank capacity (l) 29,5
Depression (Kpa) 25
Flow (l/min) 4500
Sound level (dBA) 60
Atex Zone 22 No
Accessory diameter (mm) 36
Unclogging automatic
Class-H approved Yes
Vacuum cleaner filter Class M PTFE + HEPA for Class H
Synchro socket Yes
Cable length (m) 7,5
Tank capacity (L) 42