



Photo et textes non contractuels

## PRO 32 PC

(Ref. 20502089)

Drilling metals, plastic materials and wood

**Intensive usage**

Guarantee:  

### Product Information:

Steel cast iron frame, head and stand V-belt  
Transmission with tension adjustment  
Spindle fitted on bearings  
Adjustable spindle mack motion through return spring  
Drilling-depth stop  
Steel column  
Very low voltage controls 24 V  
Emergency Stop through mushroom stay put button  
Safety microswitch of the pulley cover  
Servo polycarbonate screen  
Rack-driven table

### Supplied with:

- Key less chuck 16 mm
- Chuck shank
- Taper drift
- Screw vice and set of clamps

### Technical characteristics:

Height (cm) : 176.00  
Width (cm) : 56.00  
Length (cm) : 85.00  
Net weight (Kg) : 205.00  
Power(kW) 1.1  
Power (V) 3-phase 400V  
Spindle speed (rpm) 200 - 2250  
Max. drilling capacity (mm) 32  
Morse taper MT3  
Column dia (mm) 98  
Spindle stroke (mm) 130  
Number of gears 5  
d: spindle/column distance (mm) 245  
e: spindle/base distance (mm) 1185  
f: spindle/table distance (mm) 840  
Table dimension (mm) 410 x 380  
Distance between table grooves (mm) 185  
Lighting No  
Servo screen Yes  
Reversible vice table No  
Coolant No  
Jaw width (mm) 150  
Jaw height (mm) 25  
Opening (mm) 140  
Automatic down motion (mm/tr) No  
Slow down motion No  
Semi automatic tapping No  
Cross motion table No