



## 119 FR

(Ref. 20113036)

Dry grinding of ferrous metals  
**Usage très intensif**

Guarantee:  

Photo et textes non contractuels

### Product Information:

"Cast aluminium body  
Fitted with self-lubricated oiltight bearings  
Electrical brake powered by an Emergency Stop, stop in less than 5 seconds  
Control box complying with high school and administration requirements  
24V very low voltage controls :  
Start/Stop  
Switching on lamp  
Emergency stops  
Lack of voltage-coil safety device  
Polycarbonate protective shield  
Motor internal automatic heat protection  
Pressed metal sheet carters fitted with a nozzle to collect dust  
Adjustable anti-spark shield and tool-holders 2 mm away from the wheel  
Hot weather adaptation on request  
3-phase 230V version of the bench grinder on request"

### Supplied with:

- Grinding Wheel A 24 R
- Grinding Wheel A 60 M

### Technical characteristics:

Height (cm) : 54.50  
Width (cm) : 25.00  
Length (cm) : 42.00  
Net weight (Kg) : 25.00  
Power(kW) 0.55  
Power (V) 3-phase 400V  
Rotation speed 1 (rpm) 2 800  
Wheel-1 dimension (mm) 150 x 20 x 16  
Wheel-1 grain A 24 R / A 60 M  
Diameter (mm)