



SR 276 DA

(Ref. 20114110)

Dry steel sawing with coolant
Usage régulier

Guarantee:  **3** 

Photo et textes non contractuels

Product Information:

"Steel cast iron arch
Band guides fitted with bearings and carbide tips ensuring a good wear resistance to band
Adjustable front mobile band guide
Gravity-feed separate down move through oil cylinder
2-point lubrication system through electropump
Band-tension microswitch and pressure gauge
Rapid clamping vice monté sur glissière à rattrapage de jeu
Front control panel
24V very low voltage controls
Emergency Stop through mushroom stay put button
Band cover fitted with a positive microswitch
Motor protection through thermal circuit breaker
Coaxial reducer motor"

Technical characteristics:

Height (cm) : 169.00
Width (cm) : 173.00
Length (cm) : 110.00
Net weight (Kg) : 188.00
Power(kW) 0.6 / 1.1
Power (V) 3-phase 400V
Speed (m/min) 45 / 90
Round cutting capacity (mm) at 90° 225
Square cutting capacity (mm) at 90° 190
Rectangle cutting capacity (mm) at 90° 230 x 145
Left round cutting capacity (mm) at 45° 145
Left square cutting capacity (mm) at 45° 145
Left rectangle cutting capacity (mm) at 45° 130 x 220
Left round cutting capacity (mm) at 60° 90
Left square cutting capacity (mm) at 60° 90
Left rectangle cutting capacity (mm) at 60° 110 x 90
Vice opening (mm) 245
Working height (mm) 890
Tape (mm) 2480 x 27 x 0.9