



SR 211 DAV

(Ref. 20114130)

Dry steel, stainless steel and aluminium sawing with coolant with coolant

Usage régulier

Guarantee:  

Photo et textes non contractuels

Product Information:

Steel cast iron arch
Band guides fitted with bearings ensuring an excellent wear-resistance of band saw blade
Adjustable front mobile band guide
Gravity-feed separate down move through oil cylinder
2-point lubrication system through electropump
Band-tension microswitch and pressure gauge
Fast-tightening vice mounted on clearance catch-up slide
Electronic speed variator
Front control panel
24V very low voltage controls
Emergency Stop through mushroom stay put button

Band cover fitted with a positive microswitch
Motor protection through thermal circuit breaker
Coaxial reducer motor

Comes with:

- base
- band saw blade
- 500 mm adjustable cut stop

Technical characteristics:

Height (cm) : 160.00
Width (cm) : 146.00
Length (cm) : 100.00
Net weight (Kg) : 155.00
Power(kW) 1.5
Power (V) 1-phase 230V
Speed (m/min) 20 : 90
Round cutting capacity (mm) at 90° 170
Square cutting capacity (mm) at 90° 170
Rectangle cutting capacity (mm) at 90° 200 x 160
Left round cutting capacity (mm) at 45° 110
Left square cutting capacity (mm) at 45° 110
Left rectangle cutting capacity (mm) at 45° 125 x 85
Vice opening (mm) 200
Working height (mm) 880
Tape (mm) 2080 x 20 x 0.9