



## PRECICUT 350 PLUS

(Ref. 20116000)

Dry or water electric cutting of tiles et Materials  
**Usage régulier**

Guarantee:  

Photo et textes non contractuels

### Product Information:

Machine designed to perform precise cuts of material for buildings structural works  
Mobile-table machine  
Fitting diamond disk - diameters 300 or 350 mm  
Disk cooling down on both faces  
Adjustable-height and tilting head to perform bevelled cuts  
Supporting scale with orientable cutting stop  
Cooling circuit of the disk with electric pump with an adjustable-cutting-off knob to ensure a better efficiency  
Roller-carriage moving on rails separated from the frame  
Anti-tilting device of the carriage  
Aluminium frame  
Folding feet under the frame  
Transport wheels of the machine

### Technical characteristics:

Height (cm) : 58.50  
Width (cm) : 84.00  
Length (cm) : 122.00  
Net weight (Kg) : 81.00  
Power (W) 2200  
Power (V) 1-phase 230V  
Rotation speed (rpm) 2800  
Disk diameter (mm) 300 / 350  
Disk bore (mm) 25.4  
Length cutting capacity (mm) 90° 630  
Height cutting capacity (mm) 90° 100  
Left height cutting capacity (mm) 45° 630  
Left height cutting capacity (mm) 45° 60  
Water tank (l) 45  
Tile thickness (mm) 20

### Standard delivered accessories:

Single-phase female socket (without power cable)  
Disk mount key  
Disk lock axis  
Flat wrench 13 mm  
Delivery WITHOUT diamond disc