



## JET 50 P

(Ref. 20402046)

Water and dust suction  
**Usage très intensif**

Norm: EN 60335-2-69

Guarantee:  

Photo et textes non contractuels

### Product Information:

"Manual unclogging system of the filter using a single button  
Water-resistant high-efficiency 9.9% Class M cartridge filter  
Metal accessories and stainless steel tubes  
Storage unit of accessories integrated to the base  
Large 2-wheel + 2 castors for a stabilised stability  
Anti-crushing shielded hose  
Dual-turbine suction  
By-pass cooling down system motor designed for heavy-duty jobs (air is sucked by a third turbine on top of the motor, only for cooling down)  
Anti-static electricity plate connected to earth  
Neoprene power cable HO7 RNF length 7 m"

#### "Standard accessories:

- Bent tubes 2 x 500 mm Ø 40 mm
- hose Ø 40 mm, length 2.5 m
- Dust nozzle - 400 mm
- liquid nozzle - 400 mm
- round brush
- flat nozzle
- round brush fitting
- Class M cartridge filter PTFE

### Technical characteristics:

Height (cm) : 92.00  
Width (cm) : 52.00  
Length (cm) : 63.00  
Net weight (Kg) : 27.00  
Power (W) 1200  
Power (V) 1-phase 230V  
Tank Polypropylene  
Tank capacity (l) 50  
Depression (Kpa) 23.52  
Flow (l/min) 3 600  
Sound level (dBA) 76  
Atex Zone 22 No  
Accessory diameter (mm) 40  
Unclogging Yes  
Class-M approved No  
Vacuum cleaner filter Class M PET cartridge  
Synchro socket No  
Cable length (m) 7  
Tank capacity (L) 78