



Photo et textes non contractuels

## MC 30 i

(Ref. 20403005)

Water and dust suction  
**Usage régulier**

Norm: EN 60335-2-69

Guarantee:  

### Product Information:

"Fitted with a class L filter  
Anti-crushing shielded hose  
4-wheel stand for optimised motion  
Dual turbine suction  
By-pass cooling motor (air is sucked up by a third turbine on top of the motor, only for cooling down). Designed for heavy-duty jobs  
Vinyl power cable H05 VV-F length 7 m

#### Standard accessories:

- telescopic steel tube Ø 32 mm
- dual-purpose dust nozzle
- liquid nozzle
- round brush
- flat nozzle
- padding nozzle
- hose, length 2,6 m Ø 32 mm

### Technical characteristics:

Height (cm) : 41.00  
Width (cm) : 41.00  
Length (cm) : 75.00  
Net weight (Kg) : 12.00  
Repairability index 7,6/10  
Power (W) 1000  
Power (V) 1-phase 230V  
Tank stainless steel  
Tank capacity (l) 35  
Depression (Kpa) 22.54  
Flow (l/min) 3 530  
Sound level (dBA) 69.5  
Atex Zone 22 No  
Accessory diameter (mm) 32  
Unclogging No  
Class-M approved No  
Vacuum cleaner filter Class L  
Synchro socket No  
Cable length (m) 7  
Tank capacity (L) 38