



30 CVTE

(Ref. 20502066)

Drilling and tapping of metals, plastic materials and wood, with coolant

Usage intensif

Guarantee:  

Photo et textes non contractuels

Product Information:

Steel cast iron frame, head and stand
Steel column
Transmission through Poly V belts with tension adjustment
Spindle fitted on bearings
Adjustable spindle rack motion through return spring
Drilling-depth stop
Electronic speed variator
Digital display of the spindle speed
Controls : Emergency Stop through mushroom stop button, Safety microswitch of the pulley cover, Spindle speed override button
Servo detachable chuck protective shield
LED lighting 12 V - 6 W
2-position reversible vice table, vernier
Vice fitted on guideways
Rack-driven table

Supplied with:

-Self-clamping chuck,
-Chuck shank,
-Taper drift

Technical characteristics:

Height (cm) : 175.00
Width (cm) : 77.00
Length (cm) : 65.00
Net weight (Kg) : 198.00
Power(kW) 1.5
Power (V) 3-phase 400V
Spindle speed (rpm) 100 : 2500
Max. drilling capacity (mm) 30
Morse taper MT3
Column dia (mm) 92
Spindle stroke (mm) 125
Number of gears Variables
d: spindle/column distance (mm) 209
e: spindle/base distance (mm) 1 150
f: spindle/table distance (mm) 200 - 750
Table dimension (mm) 395 x 285
Distance between table grooves (mm) 105
Lighting Yes
Servo screen Yes
Reversible vice table Yes
Coolant Yes
Jaw width (mm) 120
Jaw height (mm) 53
Opening (mm) 100
Automatic down motion (mm/tr) No
Slow down motion No
Semi automatic tapping No
Cross motion table No