



## 75 PM B +

(Ref. 20502071)

Drilling, drill-coring and tapping steel with coolant  
**Usage intensif**

Guarantee:  

Photo et textes non contractuels

### Product Information:

- Robust and versatile magnetic drilling machine
- 4 gears through gears
- Inversion of rotational direction to tap M3 to M14
- MT3 Spindle
- Protective shield
- Left/Right 15° side rotation base
- Forward/Backwards motion base (20 mm)
- Built-in coolant tank
- Coolant through tool center

### Supplied with:

- Set of mills HSS Weldom 19mm diamètre 12-14-16-18-20-22 mm
- Mill-holder shaft Weldon 19 mm
- Chuck fitting
- Wrench chuck 16 mm for drill- Transport case
- Safety chain
- Outils

### Technical characteristics:

- Height (cm) : 60.00
- Width (cm) : 37.00
- Length (cm) : 30.00
- Net weight (Kg) : 27.00
- Power(kW) 1.8
- Power (V) 1-phase 230V
- Load speed (rpm) 90 / 120 / 180 / 230
- Mill (D x Length maxi) 75
- Drill 32
- Taps M25
- Spindle stroke (mm) 145
- Magnetic force (N) 32 000
- Basic dimension (mm) 200 x 100
- Box of mills Yes
- Mill Max. machining Ø 75
- Drill Max. machining Ø 32
- Tap Max. machining Ø M25