



PRO 30FVDLT

(Ref. 20502081)

Drilling, tapping, milling metals, plastic materials and wood, (with coolant)

Usage intensif

Guarantee:  

Photo et textes non contractuels

Product Information:

Massive steel cast iron bed, head and base
Adulid-tailed prismatic column
6 speed per mechanical gearbox
Semi-automatic tapping system - instant return
Fine feed
Cross-moving table
Gear head $\pm 90^\circ$ swiveling
Very low voltage controls 24 V
Stop punch to hook
3-point locking sectioner
LED lighting 24 V

Supplied with:

- Stand
- Pulling 405 mm M16
- Toolbox
- Service key set
- Lifting eyelets
- Self-tightening 16 mm mandrin
- Chuck arbor
- Drift key
- Vice EBT100 and clamps

Technical characteristics:

Height (cm) : 206.00
Width (cm) : 88.00
Length (cm) : 96.00
Net weight (Kg) : 453.00
Power(kW) 0.75
Power (V) 3-phase 400V
Spindle speed (rpm) 50 : 1250
Max. drilling capacity (mm) 30
Max. tapping capacity (mm) M8 - M20
Milling capacity (mm) 60
Morse taper MT3
Spindle stroke (mm) 120
Number of gears 6
d: spindle/column distance (mm) 290
f: spindle/table distance (mm) 420
Table dimension (mm) 725 x 210
Distance between table grooves (mm) 2 x 57
Lighting Yes
Servo screen Yes
Reversible vice table No
Coolant Yes
Jaw width (mm) 100
Jaw height (mm) 38
Opening (mm) 62
Transversal / longitudinal stroke (mm) 435 x 255
Automatic down motion (mm/tr) No
Slow down motion Yes
Semi automatic tapping Yes
Cross motion table Yes