



PRO 22 PEVT

(Ref. 20502085)

Dry drilling of metals, plastic materials and wood (lubrification en option)

Usage intensif

Guarantee:  

Photo et textes non contractuels

Product Information:

- Steel cast iron frame, head and stand
- Steel column
- Transmission through Poly V belts with tension adjustment
- Spindle fitted on bearings
- Adjustable spindle rack motion through return spring
- Drilling-depth stop
- Semi automatic tapping system
- Electronic speed variator
- Digital display of the spindle speed
- Emergency Stop through mushroom stay put button
- Safety microswitch of the pulley cover
- Spindle speed override button
- Servo detachable chuck protective shield
- LED lighting 3.6 V - 3 W
- Tilting table up to 45° with a vernier and a coolant collector + 12-mm table grooves
- Rack-driven table

Supplied with:

- Tap chuck M3 to M12
- Key-less chuck 16 mm
- Chuck shank
- Taper drift
- Vice BSF 120 and clamp set

Technical characteristics:

- Height (cm) : 108.50
- Width (cm) : 72.00
- Length (cm) : 37.00
- Net weight (Kg) : 101.68
- Power(kW) 1.2
- Power (V) 1-phase 230V
- Spindle speed (rpm) 150 : 2500
- Max. drilling capacity (mm) 22
- Max. tapping capacity (mm) M10
- Morse taper MT2
- Column dia (mm) 80
- Spindle stroke (mm) 90
- Number of gears Variable
- d: spindle/column distance (mm) 180
- e: spindle/base distance (mm) 650
- f: spindle/table distance (mm) 140 - 425
- Table dimension (mm) 280 x 280
- Lighting Yes
- Servo screen Yes
- Reversible vice table No
- Coolant No
- Automatic down motion (mm/tr) No
- Slow down motion No
- Semi automatic tapping Yes
- Cross motion table No