



## SPC 40 TC VEL DL T

(Ref. 20601147)

Drilling metals, plastic materials and wood, with coolant  
**Usage très intensif**

Guarantee:  **3** 

Photo et textes non contractuels

### Product Information:

Semi automatic tapping  
 Cross move table  
 Electronic speed variator  
 Slow down motion  
 Steel cast iron frame, head and stand  
 Steel column  
 Machined aluminium pulleys  
 Transmission through V belts with rapid adjustment of tension  
 Spindle fitted on bearings  
 Adjustable spindle rack motion through return spring  
 24V very low voltage controls :  
 - ON/OFF  
 - Switching on lamp  
 - Emergency Stop through mushroom stay put button  
 - 3-point locking circuit breaker  
 Detachable servo protective shield  
 24V lighting  
 Electrical protection IP54  
 Noise level 50 dB  
 Rack-driven table, graisseur de la vis sans fin

### Technical characteristics:

Height (cm) : 185.00  
 Width (cm) : 47.50  
 Length (cm) : 90.00  
 Net weight (Kg) : 410.00  
 Power(kW) 0.8 / 1.47  
 Power (V) 3-phase 400V  
 Spindle speed (rpm) 80 - 2030  
 Max. drilling capacity (mm) 40  
 Milling capacity (mm) 80  
 Morse taper MT4  
 Column dia (mm) 140  
 Spindle stroke (mm) 150  
 Number of gears 14  
 d: spindle/column distance (mm) 300  
 e: spindle/base distance (mm) 1 150  
 f: spindle/table distance (mm) 50-610  
 Table dimension (mm) 300 x 540  
 Distance between table grooves (mm) 150  
 Lighting Yes  
 Servo screen Yes

Hot weather adaptation on request  
Can be modified to 230V three-phase on request  
Machined aluminium pulleys

Transversal / longitudinal stroke (mm) 300 x 410  
Automatic down motion (mm/tr) No  
Slow down motion Yes  
Semi automatic tapping Yes  
Cross motion table Yes

**Supplied with Self-clamping chuck and Chuck shank**