



Photo et textes non contractuels

## Product Information:

"Electronic speed variator  
Very highly rigid steel cast iron arch  
Band guides fitted with bearings and carbide tips ensuring a good wear resistance to band  
Adjustable front mobile band guide  
2-point lubrication system through electropump  
Vice support tilting with the arch  
Rapid clamping vice monté sur glissière à rattrapage de jeu  
24V very low voltage controls  
Emergency Stop through mushroom stay put button  
Band cover fitted with a microswitch  
Motor protection through thermal circuit breaker  
Electrical protection IP54  
Coaxial reducer motor  
Oil cylinder controlling the down move of the arch through a gravity-feed system"

## SR 374 DG DAV

(Ref. 20114102)

Dry steel, stainless steel and aluminium sawing with coolant with coolant

**Usage intensif**

Guarantee: CE

## Technical characteristics:

Height (cm) : 155.00  
Width (cm) : 96.00  
Length (cm) : 178.00  
Net weight (Kg) : 595.00  
Power(kW)  
Power (V) 3-phase 400V  
Speed (m/min)  
Round cutting capacity (mm) at 90°  
Square cutting capacity (mm) at 90°  
Rectangle cutting capacity (mm) at 90°  
Left round cutting capacity (mm) at 45°  
Left square cutting capacity (mm) at 45°  
Left rectangle cutting capacity (mm) at 45°  
Left round cutting capacity (mm) at 60°  
Left square cutting capacity (mm) at 60°  
Left rectangle cutting capacity (mm) at 60°  
Vice opening (mm)  
Working height (mm)  
Tape (mm)  
Right rectangle cutting capacity (mm) at 45°  
Right round cutting capacity (mm) at 45°  
Left square cutting capacity (mm) at 45°