



SR 374 DG DAV

(Ref. 20114102)

Dry steel, stainless steel and aluminium sawing with coolant with coolant

Usage intensif

Guarantee:  

Photo et textes non contractuels

Product Information:

"Electronic speed variator
Very highly rigid steel cast iron arch
Band guides fitted with bearings and carbide tips ensuring a good wear resistance to band
Adjustable front mobile band guide
2-point lubrication system through electropump
Vice support tilting with the arch
Rapid clamping vice monté sur glissière à rattrapage de jeu
24V very low voltage controls
Emergency Stop through mushroom stay put button
Band cover fitted with a microswitch
Motor protection through thermal circuit breaker
Electrical protection IP54
Coaxial reducer motor
Oil cylinder controlling the down move of the arch through a gravity-feed system"

Technical characteristics:

Height (cm) : 155.00
Width (cm) : 96.00
Length (cm) : 178.00
Net weight (Kg) : 595.00
Power(kW) 2.2
Power (V) 3-phase 400V
Speed (m/min) 15 : 90
Round cutting capacity (mm) at 90° 300
Square cutting capacity (mm) at 90° 290
Rectangle cutting capacity (mm) at 90° 370 x 185
Left round cutting capacity (mm) at 45° 240
Left square cutting capacity (mm) at 45° 220
Left rectangle cutting capacity (mm) at 45° 240 x 100
Left round cutting capacity (mm) at 60° 150
Left square cutting capacity (mm) at 60° 145
Left rectangle cutting capacity (mm) at 60° 150 x 100
Vice opening (mm) 375
Working height (mm) 915
Tape (mm) 3150 x 27 x 0.9
Right rectangle cutting capacity (mm) at 45° 240 x 100
Right round cutting capacity (mm) at 45° 220
Left square cutting capacity (mm) at 45° 190