



## SR 276 DAV

(Ref. 20114112)

Dry steel, stainless steel and aluminium sawing with coolant with coolant

**Usage régulier**

Guarantee:  

Photo et textes non contractuels

### Product Information:

"Steel cast iron arch  
Band guides fitted with bearings and carbide tips ensuring a good wear resistance to band  
Adjustable front mobile band guide  
Gravity-feed separate down move through oil cylinder  
2-point lubrication system through electropump  
Band-tension microswitch and pressure gauge  
Rapid clamping vice monté sur glissière à rattrapage de jeu  
Band speed variator  
Front control panel  
24V very low voltage controls  
Emergency Stop through mushroom stay put button  
Band cover fitted with a positive microswitch  
Motor protection through thermal circuit breaker  
Coaxial reducer motor"

### Technical characteristics:

Height (cm) : 169.00  
Width (cm) : 173.00  
Length (cm) : 110.00  
Net weight (Kg) : 188.00  
Power(kW) 1.5  
Power (V) 3-phase 400V  
Speed (m/min) 20 : 90  
Round cutting capacity (mm) at 90° 225  
Square cutting capacity (mm) at 90° 190  
Rectangle cutting capacity (mm) at 90° 230 x 145  
Left round cutting capacity (mm) at 45° 145  
Left square cutting capacity (mm) at 45° 145  
Left rectangle cutting capacity (mm) at 45° 130 x 220  
Left round cutting capacity (mm) at 60° 90  
Left square cutting capacity (mm) at 60° 90  
Left rectangle cutting capacity (mm) at 60° 110 x 90  
Vice opening (mm) 245  
Working height (mm) 890  
Tape (mm) 2480 x 27 x 0.9