



SR 374 DG SAV

(Ref. 20114117)

Dry steel, stainless steel and aluminium sawing with coolant with coolant

Usage intensif

Guarantee:  

Photo et textes non contractuels

Product Information:

- "Fully-hydraulic semi automatic cycle of band, arch and arch
- Electronic speed variator
- Semi automatic down move of the arch
- Very highly rigid steel cast iron arch
- Band guides fitted with bearings and carbide tips ensuring a good wear resistance to band
- Adjustable front mobile band guide
- 2-point lubrication system through electropump
- Vice support tilting with the arch
- Hydraulic vice
- 24V very low voltage controls
- Emergency Stop through mushroom stay put button
- Band cover fitted with a microswitch
- Motor protection through thermal circuit breaker
- Electrical protection IP54
- Coaxial reducer motor

Technical characteristics:

- Height (cm) : 200.00
- Width (cm) : 230.00
- Length (cm) : 155.00
- Net weight (Kg) : 665.00
- Power(kW) 2.2
- Power (V) 3-phase 400V
- Speed (m/min) 15 : 90
- Round cutting capacity (mm) at 90° 300
- Square cutting capacity (mm) at 90° 290
- Rectangle cutting capacity (mm) at 90° 370 x 185
- Left round cutting capacity (mm) at 45° 240
- Left square cutting capacity (mm) at 45° 220
- Left rectangle cutting capacity (mm) at 45° 240 x 100
- Left round cutting capacity (mm) at 60° 150
- Left square cutting capacity (mm) at 60° 145
- Left rectangle cutting capacity (mm) at 60° 150 x 100
- Vice opening (mm) 375
- Working height (mm) 915
- Tape (mm) 3150 x 27 x 0.9
- Right rectangle cutting capacity (mm) at 45° 240 x 100
- Right round cutting capacity (mm) at 45° 220
- Left square cutting capacity (mm) at 45° 190