



SR 320 DG DAV

(Ref. 20114127)

Usage intensif

Guarantee:  

Photo et textes non contractuels

Product Information:

- Left and right cutting
- Electronic speed variator
- Autonomous down move of the arch
- Very highly rigid steel cast iron arch
- Band guides fitted with bearings and carbide tips ensuring a good wear resistance to band
- Adjustable front mobile band guide
- 2-point lubrication system through electropump
- Vice support tilting with the arch
- Hydraulic vice
- 24V very low voltage controls
- Emergency Stop through mushroom stay put button
- Band cover fitted with a microswitch
- Motor protection through thermal circuit breaker
- Electrical protection IP54
- Coaxial reducer motor

Supplie with:

- base
- band saw
- adjustable cut stop

Technical characteristics:

- Height (cm) : 150.00
- Width (cm) : 80.00
- Length (cm) : 175.00
- Net weight (Kg) : 417.00
- Power(kW) 2,2
- Power (V) 3-phase 400V
- Speed (m/min) 20 : 80
- Round cutting capacity (mm) at 90° 270
- Square cutting capacity (mm) at 90° 260
- Rectangle cutting capacity (mm) at 90° 260 x 320
- Left round cutting capacity (mm) at 45° 230
- Left square cutting capacity (mm) at 45° 220
- Left rectangle cutting capacity (mm) at 45° 220 x 220
- Left round cutting capacity (mm) at 60° 140
- Left square cutting capacity (mm) at 60° 140
- Left rectangle cutting capacity (mm) at 60° 140 x 140
- Vice opening (mm) 270
- Working height (mm) 980
- Tape (mm) 2925 x 27 x 0.9
- Right rectangle cutting capacity (mm) at 45° 220 x 150
- Right round cutting capacity (mm) at 45° 175
- Left square cutting capacity (mm) at 45° 200