



## SR 285 DG SAV

(Ref. 20114128)

Dry steel, stainless steel and aluminium sawing with coolant with coolant

**Usage intensif**

Guarantee:  

Photo et textes non contractuels

### Product Information:

- Fully-hydraulic semi automatic cycle of band, arch and arch
- Electronic speed variator
- Semi automatic down move of the arch
- Very highly rigid steel cast iron arch
- Band guides fitted with bearings and carbide tips ensuring a good wear resistance to band
- Adjustable front mobile band guide
- 2-point lubrication system through electropump
- Vice support tilting with the arch
- Hydraulic vice
- 24V very low voltage controls
- Emergency Stop through mushroom stay put button
- Band cover fitted with a microswitch
- Motor protection through thermal circuit breaker
- Electrical protection IP54
- Coaxial reducer motor

### Supplied with:

- base
- band saw
- adjustable cut stop

### Technical characteristics:

- Height (cm) : 105.40
- Width (cm) : 75.00
- Length (cm) : 167.60
- Net weight (Kg) : 310.00
- Power(kW) 1,1
- Power (V) 3-phase 400V
- Speed (m/min) 20 : 85
- Round cutting capacity (mm) at 90° 240
- Square cutting capacity (mm) at 90° 240
- Rectangle cutting capacity (mm) at 90° 200 x 285
- Left round cutting capacity (mm) at 45° 200
- Left square cutting capacity (mm) at 45° 180
- Left rectangle cutting capacity (mm) at 45° 140 x 180
- Left round cutting capacity (mm) at 60° 120
- Left square cutting capacity (mm) at 60° 95
- Left rectangle cutting capacity (mm) at 60° 95 x 110
- Vice opening (mm) 375
- Working height (mm) 915
- Tape (mm) 2685 x 27 x 0.9
- Right rectangle cutting capacity (mm) at 45° 90 x 150
- Right round cutting capacity (mm) at 45° 150
- Left square cutting capacity (mm) at 45° 140