

PRODUCT SHEET | Update File: 11/27/2025

BANDSAWS | Separate down-move band saw



Photo et textes non contractuels

EXPERT 250 SR DGDA

(Ref. 20114136)

Dry steel sawing with coolant Usage régulier

Guarantee: 🕃 🤾



Product Information:

Cuts left and right

Aircast fram

Saw blade guides equipped with bearings and carbide pads to ensure exc

ellent resistance to saw blade wear

Adjustable anterior tape guide

Autonomous descent by gravity controlled by hydraulic cylinder

2-point electro-pump lubrication device

Safety micro-switch and tension gauge saw blade

Fast-tightening set mounted on game catch-up slide

Control desk in front

Very low voltage controls 24 V

Stopping punch to hook

Carter saw equipped with a positive micro-reuptor

Motor protection by heat breaker

Motor with coaxial gearbox

Supplied with base, saw blade and 500 mm adjustable cut stop

Technical characteristics:

Height (cm): 180.00 Width (cm): 100.00 Length (cm): 185.00

Net weight (Kg): 306.00

Power(kW)

Power (V) 3-phase 400V

Speed (m/min)

Round cutting capacity (mm) at 90 Squre cutting capacity (mm) at 90° Rectangle cutting capacity (mm) at 90° Left round cutting capacity (mm) at 45° Left square cutting capacity (mm) at 45° Left rectangle cutting capacity (mm) at 45° Left round cutting capacity (mm) at 60° Left square cutting capacity (mm) at 60° Left rectangle cutting capacity (mm) at 60° Vice opening (mm) Working height (mm) Tape (mm)

Right rectangle cutting capacity (mm) at 45° Right round cutting capacity (mm) at 45° Left square cutting capacity (mm) at 45°