



JET 30 i

(Ref. 20402041)

Water and dust suction

Usage très intensif

Norm: EN 60335-2-69

Guarantee:  

Photo et textes non contractuels

Product Information:

"Manual unclogging system of the filter using a single button
 Water-resistant high-efficiency 9.9% Class M cartridge filter
 Metal accessories and stainless steel tubes
 Carbon-fibre reinforced base
 Storage unit of accessories integrated to the base
 Large reinforced 2-wheel + 2-caster base for an optimised stability
 Anti-crushing shielded hose
 By-pass cooling down system 1450W motor designed for continuous heavy-duty jobs (air is sucked by a third turbine on top of the motor, only for cooling down)
 Suction, depression and cutting-off high-performance Anti-static electricity plate connected to earth
 Neoprene power table HO7 RNF length 7 m"

Technical characteristics:

Height (cm) : 80.00
 Width (cm) : 54.00
 Length (cm) : 45.00
 Net weight (Kg) : 16.60
 Power (W)
 Power (V) 1-phase 230V
 Tank stainless steel
 Tank capacity (l)
 Depression (Kpa) 26.7
 Flow (l/min)
 Sound level (dBA)
 Atex Zone 22 No
 Accessory diameter (mm)
 Unclogging Yes
 Class-M approved No
 Vacuum cleaner filter Class M PET cartridge
 Synchro socket No
 Cable length (m)
 Tank capacity (L)

Standard accessories:

- Bent tubes 2 x 500 mm Ø 40 mm
- hose Ø 40 mm, length 2.5 m
- Dust nozzle - 400 mm
- liquid nozzle - 400 mm
- round brush
- flat nozzle
- round brush fitting
- Class M cartridge filter PTFE