



JET 50 i

(Ref. 20402043)

Water and dust suction
Usage très intensif

Norm: EN 60335-2-69

Guarantee:  

Photo et textes non contractuels

Product Information:

"Manual unclogging system of the filter using a single button
Water-resistant high-efficiency 9.9% Class M cartridge filter
Metal accessories and stainless steel tubes
Aluminium base with large built-in handle
Storage unit of accessories integrated to the base
Large reinforced 2-wheel + 2-caster base for an optimised stability
Anti-crushing shielded hose
Dual-turbine suction
By-pass cooling down system motor designed for heavy-duty jobs (air is sucked by a third turbine on top of the motor, only for cooling down)
Anti-static electricity plate connected to earth
Neoprene power table HO7 RNF length 7 m"

"Standard accessories:

- Bent tubes 2 x 500 mm Ø 40 mm
- hose Ø 40 mm, length 2.5 m
- Dust nozzle - 400 mm
- liquid nozzle - 400 mm
- round brush
- flat nozzle
- round brush fitting
- Class M cartridge filter PTFE

Technical characteristics:

Height (cm) : 103.00
Width (cm) : 56.00
Length (cm) : 61.00
Net weight (Kg) : 28.40
Power (W) 1200
Power (V) 1-phase 230V
Tank stainless steel
Tank capacity (l) 50
Depression (Kpa) 23.52
Flow (l/min) 3 600
Sound level (dBA) 76
Atex Zone 22 No
Accessory diameter (mm) 40
Unclogging Yes
Class-M approved No
Vacuum cleaner filter Class M PET cartridge
Synchro socket No
Cable length (m) 7
Tank capacity (L) 78