



## MC 16 i

(Ref. 20403004)

Water and dust suction

**Usage régulier**

Norm: EN 60335-2-69

Guarantee:  

Photo et textes non contractuels

### Product Information:

- Fitted standard with a class L filter
- Anti-crushing shielded hose
- 4-wheel stand for optimised motion
- Dual turbine suction
- By-pass cooling motor (air is sucked up by a third turbine on top of the motor, only for cooling down)
- Motor designed for heavy-duty jobs
- Vinyl power cable H05 VV-F length 7 m

#### Standard accessories:

- telescopic steel tube Ø 32 mm
- dual-purpose dust nozzle
- liquid nozzle
- round brush
- flat nozzle
- padding nozzle
- hose, length 2,6 m Ø 32 mm

### Technical characteristics:

- Height (cm) : 58.00
- Width (cm) : 40.00
- Length (cm) : 40.00
- Net weight (Kg) : 11.00
- Repairability index 7,2/10
- Power (W) 1000
- Power (V) 1-phase 230V
- Tank stainless steel
- Tank capacity (l) 20
- Depression (Kpa) 22.54
- Flow (l/min) 3 530
- Sound level (dBA) 69.5
- Atex Zone 22 No
- Accessory diameter (mm) 32
- Unclogging No
- Class-M approved No
- Vacuum cleaner filter Class L
- Synchro socket No
- Cable length (m) 7
- Tank capacity (L) 23