



Photo et textes non contractuels

MC 30 i

(Ref. 20403005)

Water and dust suction

Usage régulier

Norm: EN 60335-2-69

Guarantee:  

Product Information:

"Fitted with a class L filter
Anti-crushing shielded hose
4-wheel stand for optimised motion
Dual turbine suction
By-pass cooling motor (air is sucked up by a third turbine on top of the motor, only for cooling down). Designed for heavy-duty jobs
Vinyl power cable H05 VV-F length 7 m

Standard accessories:

- telescopic steel tube Ø 32 mm
- dual-purpose dust nozzle
- liquid nozzle
- round brush
- flat nozzle
- padding nozzle
- hose, length 2,6 m Ø 32 mm

Technical characteristics:

Height (cm) : 41.00
Width (cm) : 41.00
Length (cm) : 75.00
Net weight (Kg) : 12.00
Repairability index 7,6/10
Power (W) 1000
Power (V) 1-phase 230V
Tank stainless steel
Tank capacity (l) 35
Depression (Kpa) 22.54
Flow (l/min) 3 530
Sound level (dBA) 69.5
Atex Zone 22 No
Accessory diameter (mm) 32
Unclogging No
Class-M approved No
Vacuum cleaner filter Class L
Synchro socket No
Cable length (m) 7
Tank capacity (L) 38