



Photo et textes non contractuels

STAR 13 PE

(Ref. 20501016)

Dry drilling of metals, plastic materials and wood
Usage d'appoint

Guarantee:  

Product Information:

Steel cast iron column
V-belt transmission
Spindle fitted on bearings
ON/OFF switch fitted with a lack of voltage coil
Safety microswitch around belt cover
Tilting and adjustable protective shield
Tilting table up to 45°

Supplied with:

- Self-clamping chuck 13 mm
- Screw vice and set of clamps

Technical characteristics:

Height (cm) : 58.00
Width (cm) : 23.00
Length (cm) : 43.00
Net weight (Kg) : 17.80
Power(kW) 0.3
Power (V) 1-phase 230V
Spindle speed (rpm) 520-2620
Max. drilling capacity (mm) 13
Morse taper B16
Column dia (mm) 48
Spindle stroke (mm) 50
Number of gears 5
d: spindle/column distance (mm) 105
e: spindle/base distance (mm) 300
f: spindle/table distance (mm) 220
Table dimension (mm) 167 x 167
Distance between table grooves (mm) 110
Lighting No
Servo screen No
Reversible vice table No
Coolant No
Automatic down motion (mm/tr) No
Slow down motion No
Semi automatic tapping No
Cross motion table No