



## STAR 16 PE

(Ref. 20501017)

Dry drilling of metals, plastic materials and wood  
**Usage d'appoint**

Guarantee:  

Photo et textes non contractuels

### Product Information:

Steel cast iron column  
V-belt transmission  
Spindle fitted on bearings  
ON/OFF switch fitted with a lack of voltage coil  
Emergency Stop through mushroom stay put button  
Safety-grip microswitch around belt cover  
Protective shield of servo chuck  
Tilting table up to 45 °  
Rack-driven table

### Supplied with:

- Self-clamping chuck 16 mm
- Chuck shank
- Taper drift
- Screw vice and set of clamps

### Technical characteristics:

Height (cm) : 54.00  
Width (cm) : 31.00  
Length (cm) : 85.00  
Net weight (Kg) : 32.60  
Power(kW) 0.4  
Power (V) 1-phase 230V  
Spindle speed (rpm) 200 - 2500  
Max. drilling capacity (mm) 16  
Morse taper MT2  
Column dia (mm) 60  
Spindle stroke (mm) 60  
Number of gears 12  
d: spindle/column distance (mm) 125  
e: spindle/base distance (mm) 535  
f: spindle/table distance (mm) 420  
Table dimension (mm) 200 x 200  
Distance between table grooves (mm) 112  
Lighting No  
Servo screen Yes  
Reversible vice table No  
Coolant No  
Automatic down motion (mm/tr) No  
Slow down motion No  
Semi automatic tapping No  
Cross motion table No