



30 CV

(Ref. 20502022)

Drilling and tapping of metals, plastic materials and wood, with coolant

Usage intensif

Guarantee:  

Photo et textes non contractuels

Product Information:

Steel cast iron frame, head and stand
Steel column
Spindle fitted on bearings
24V very low voltage controls
Emergency Stop through mushroom stay put button
Locking main switch 4 points
Semi automatic tapping system + instant return
Servo detachable chuck protective shield
Large table mécanicien, Rack-driven table
Electronic speed variator
Digital display of the spindle speed
LED lighting 24 V

Supplied with:

- Tap-holder chuck M3 to M16
- Self-clamping chuck 16 mm
- Chuck shank
- Taper drift
- BSH 7 vice and set of clamps

Technical characteristics:

Height (cm) : 176.50
Width (cm) : 52.50
Length (cm) : 66.00
Net weight (Kg) : 220.00
Power(kW) 1.5
Power (V) 3-phase 400V
Spindle speed (rpm) 150 : 3000
Max. drilling capacity (mm) 30
Max. tapping capacity (mm) M16
Morse taper MT3
Column dia (mm) 92
Spindle stroke (mm) 135
Number of gears Variable
d: spindle/column distance (mm) 204
e: spindle/base distance (mm) 1 150
f: spindle/table distance (mm) 185-605
Table dimension (mm) 460 x 360
Distance between table grooves (mm) 135
Lighting Yes
Servo screen Yes
Reversible vice table No
Coolant Yes
Automatic down motion (mm/tr) No
Slow down motion No
Semi automatic tapping Yes
Cross motion table No