



EXPERT 22 PCV Mono

(Ref. 20502078)

Dry drilling of metals, plastic materials and wood (lubrification en option)

Usage régulier

Guarantee:  

Photo et textes non contractuels

Product Information:

- Mechanical variable speed drive with belts
- Steel cast iron column
- Transmission through belt and steel wheels
- Spindle fitted on bearings
- ON/OFF switch fitted with a lack of voltage coil
- Emergency Stop through mushroom stay put button
- Protective shield of servo chuck
- Tilting square table up to 45°, with liquid collector
- Rack-driven table
- Digital readout of the drilling depth
- Digital display of the spindle speed
- Drilling-position laser
- LED lighting
- Pulley cover fitted with a grip-safety microswitch
- Changement des vitesses par volant à manipuler en fonctionnement

Supplied with:

- Self-clamping chuck 16 mm
- Chuck shank
- Taper drift

Technical characteristics:

- Height (cm) : 157.00
- Width (cm) : 38.00
- Length (cm) : 66.00
- Net weight (Kg) : 62.00
- Power(kW) 0.75
- Power (V) 1-phase 230V
- Spindle speed (rpm) 400 : 2000
- Max. drilling capacity (mm) 22
- Morse taper MT2
- Column dia (mm) 72
- Spindle stroke (mm) 80
- Number of gears 16
- d: spindle/column distance (mm) 180
- e: spindle/base distance (mm) 1180
- f: spindle/table distance (mm) 685
- Table dimension (mm) 305 x 305
- Distance between table grooves (mm) en croix
- Lighting Yes
- Servo screen Yes
- Reversible vice table No
- Coolant No
- Jaw width (mm) 125
- Jaw height (mm) 28
- Opening (mm) 115
- Automatic down motion (mm/tr) No
- Slow down motion No
- Semi automatic tapping No
- Cross motion table No