



Photo et textes non contractuels

16 FV

(Ref. 20502079)

Drilling, milling metals, plastic materials and wood
Usage régulier

Guarantee:  

Product Information:

Steel cast iron frame, head and stand
Dovetail column
Emergency Stop through mushroom stay put button
Left and right tilting column
Slow down motion
Servo polycarbonate screen
Cross-motion table
Table grooving
Electronic speed variator
Brushless motor

Deliver with:

- Key less 16 mm chuck
- Chuck tail
- Vice

Technical characteristics:

Height (cm) : 72.00
Width (cm) : 60.00
Length (cm) : 57.00
Net weight (Kg) : 71.00
Power(kW) 0,5
Power (V) 1-phase 230V
Spindle speed (rpm) 100 : 2500
Max. drilling capacity (mm) 16
Milling capacity (mm) 35
Morse taper MT3
Spindle stroke (mm) 180
Number of gears Variable
d: spindle/column distance (mm) 165
f: spindle/table distance (mm) 90 à 270
Table dimension (mm) 460 x 120
Distance between table grooves (mm) 35
Lighting No
Servo screen Yes
Reversible vice table No
Coolant No
Transversal / longitudinal stroke (mm) 135 x 460
Automatic down motion (mm/tr) No
Slow down motion Yes
Semi automatic tapping No
Cross motion table Yes