



Photo et textes non contractuels

## PRO 40FVDLT

(Ref. 20502082)

Drilling, tapping, milling metals, plastic materials and wood, (with coolant)

**Usage intensif**

Guarantee:  

### Product Information:

Massive steel cast iron bed, head and base  
Adulid-tailed prismatic column  
12 speed per mechanical gearbox and two stage motor  
Semi-automatic tapping system - instant return  
Fine feed  
Cross-moving table with automatic morotized advance (X axis)  
Gear head  $\pm 90^\circ$  swiveling  
Very low voltage controls 24 V  
Stop punch to hook  
3-point locking sectioner  
LED lighting 24 V

#### Supplied with:

- Stand
- Pulling 405 mm M16
- Toolbox
- Service key set
- Lifting eyelets
- Self-tightening 16 mm mandrin
- Chuck arbor
- Drift key
- Vice EBT150 and clamps

### Technical characteristics:

Height (cm) : 212.00  
Width (cm) : 85.00  
Length (cm) : 117.00  
Net weight (Kg) : 400.00  
Power(kW) 1.5  
Power (V) 3-phase 400V  
Spindle speed (rpm) 50 : 2500  
Max. drilling capacity (mm) 40  
Max. tapping capacity (mm) M8 - M25  
Milling capacity (mm) 75  
Morse taper MT4  
Spindle stroke (mm) 120  
Number of gears 12  
d: spindle/column distance (mm) 290  
f: spindle/table distance (mm) 420  
Table dimension (mm) 725 x 210  
Distance between table grooves (mm) 2 x 57  
Lighting Yes  
Servo screen Yes  
Reversible vice table No  
Coolant Yes  
Jaw width (mm) 150  
Jaw height (mm) 45  
Opening (mm) 100  
Transversal / longitudinal stroke (mm) 435 x 255  
Automatic down motion (mm/tr) No  
Slow down motion Yes  
Semi automatic tapping Yes  
Cross motion table Yes