



PRO 40 PC

(Ref. 20502090)

Drilling metals, plastic materials and wood
Usage intensif

Guarantee:  

Photo et textes non contractuels

Product Information:

- Steel cast iron frame, head and stand
- V-belt transmission with tension adjustment
- Spindle fitted on bearings
- Adjustable spindle rack motion through return spring
- Drilling-depth stop
- Steel column
- Very low voltage controls 24 V
- Emergency Stop through mushroom stop button
- Safety microswitch of the pulley cover
- Servo polycarbonate screen
- Rack-driven table

Supplied with:

- Key less chuck 16 mm
- Chuck shank
- Taper drift
- Screw vice and set of clamps

Technical characteristics:

- Height (cm) : 176.00
- Width (cm) : 56.00
- Length (cm) : 85.00
- Net weight (Kg) : 200.00
- Power(kW) 1.1
- Power (V) 3-phase 400V
- Spindle speed (rpm) 200 - 2250
- Max. drilling capacity (mm) 40
- Morse taper MT4
- Column dia (mm) 98
- Spindle stroke (mm) 130
- Number of gears 5
- d: spindle/column distance (mm) 245
- e: spindle/base distance (mm) 1185
- f: spindle/table distance (mm) 840
- Table dimension (mm) 410 x 380
- Distance between table grooves (mm) 185
- Lighting No
- Servo screen Yes
- Reversible vice table No
- Coolant No
- Jaw width (mm) 150
- Jaw height (mm) 25
- Opening (mm) 140
- Automatic down motion (mm/tr) No
- Slow down motion No
- Semi automatic tapping No
- Cross motion table No