



## EXPERT 30 PCTE

(Ref. 20502106)

Dry drilling of metals, plastic materials and wood (lubrification en option)

**Usage régulier**

Guarantee:  

Photo et textes non contractuels

### Product Information:

Steel cast iron column  
Transmission through steel dented belt and wheels  
Spindle fitted on bearings  
ON/OFF switch fitted with a lack of voltage coil  
Emergency Stop through mushroom stay put button  
Protective shield of servo chuck  
Reversible tilting vice table up to 45°, with coolant collector  
Rack-driven table  
Digital readout of the drilling depth  
Digital display of the spindle speed  
Drilling-position laser  
LED lighting  
Pulley cover fitted with a grip-safety microswitch  
Vice on guideways, 200-mm jaws, 165-mm opening

### Supplied with:

- Self-clamping chuck 16 mm
- Chuck shank
- Taper drift

### Technical characteristics:

Height (cm) : 173.00  
Width (cm) : 41.00  
Length (cm) : 76.00  
Net weight (Kg) : 130.00  
Power(kW) 1.1  
Power (V) 3-phase 400V  
Spindle speed (rpm) 150 - 2450  
Max. drilling capacity (mm) 30  
Morse taper MT3  
Column dia (mm) 92  
Spindle stroke (mm) 120  
Number of gears 12  
d: spindle/column distance (mm) 250  
e: spindle/base distance (mm) 1 215  
f: spindle/table distance (mm) 755  
Table dimension (mm) 470 x 420  
Distance between table grooves (mm) 2 x 122  
Lighting Yes  
Servo screen Yes  
Reversible vice table Yes  
Coolant No  
Jaw width (mm) 208  
Jaw height (mm) 53  
Opening (mm) 165  
Automatic down motion (mm/tr) No  
Slow down motion No  
Semi automatic tapping No  
Cross motion table No