



## EXPERT 30 PCTE

(Ref. 20502106)

Dry drilling of metals, plastic materials and wood (lubrification en option)

**Usage régulier**

Guarantee:  

Photo et textes non contractuels

### Product Information:

- Steel cast iron column
- Transmission through steel dented belt and wheels
- Spindle fitted on bearings
- ON/OFF switch fitted with a lack of voltage coil
- Emergency Stop through mushroom stay put button
- Protective shield of servo chuck
- Reversible tilting vice table up to 45°, with coolant collector
- Rack-driven table
- Digital readout of the drilling depth
- Digital display of the spindle speed
- Drilling-position laser
- LED lighting
- Pulley cover fitted with a grip-safety microswitch
- Vice on guideways, 200-mm jaws, 165-mm opening

### Supplied with:

- Self-clamping chuck 16 mm
- Chuck shank
- Taper drift

### Technical characteristics:

- Height (cm) : 173.00
- Width (cm) : 41.00
- Length (cm) : 76.00
- Net weight (Kg) : 130.00
- Power(kW) 1.1
- Power (V) 3-phase 400V
- Spindle speed (rpm) 150 - 2450
- Max. drilling capacity (mm) 30
- Morse taper MT3
- Column dia (mm) 92
- Spindle stroke (mm) 120
- Number of gears 12
- d: spindle/column distance (mm) 250
- e: spindle/base distance (mm) 1 215
- f: spindle/table distance (mm) 755
- Table dimension (mm) 470 x 420
- Distance between table grooves (mm) 2 x 122
- Lighting Yes
- Servo screen Yes
- Reversible vice table Yes
- Coolant No
- Jaw width (mm) 208
- Jaw height (mm) 53
- Opening (mm) 165
- Automatic down motion (mm/tr) No
- Slow down motion No
- Semi automatic tapping No
- Cross motion table No