



## SPC 32 TC VEL DL

(Ref. 20601131)

Drilling metals, plastic materials and wood, with coolant  
**Usage très intensif**

Guarantee:  **3** 

Photo et textes non contractuels

### Product Information:

Cross move table,  
 Slow down motion  
 Electronic speed variator  
 Steel cast iron frame, head and stand  
 Steel column  
 Machined aluminium pulleys  
 Transmission through V belts with rapid adujstment of tension  
 Spindle fitted on bearings  
 Adjustable spindle mack motion through return spring  
 24V very low voltage controls :  
 - ON/OFF  
 - Switching on lamp  
 - Emergency Stop through mushroom stay put button  
 - 3-point locking circuit breaker  
 Detachable servo protective shield  
 24V lighting  
 Electrical protection IP54  
 Noise level 50 dB  
 Rack-driven table, graisseur de la vis sans fin  
 Hot weather adaptation on request

### Technical characteristics:

Height (cm) : 180.00  
 Width (cm) : 43.50  
 Length (cm) : 88.00  
 Net weight (Kg) : 350.00  
 Power(kW) 1.5  
 Power (V) 3-phase 400V  
 Spindle speed (rpm) 80 - 2030  
 Max. drilling capacity (mm) 32  
 Milling capacity (mm) 60  
 Morse taper MT3  
 Column dia (mm) 110  
 Spindle stroke (mm) 110  
 Number of gears 14  
 d: spindle/column distance (mm) 280  
 e: spindle/base distance (mm) 1 210  
 f: spindle/table distance (mm) 50-630  
 Table dimension (mm) 240 x 600  
 Distance between table grooves (mm) 130  
 Lighting Yes  
 Servo screen Yes

Can be modified to 230V three-phase on request  
Machined aluminium pulleys

Transversal / longitudinal stroke (mm) 265 x 480  
Automatic down motion (mm/tr) No  
Slow down motion Yes  
Semi automatic tapping No  
Cross motion table Yes

**Supplied with Self-clamping chuck and Chuck shank**