



## SPC 40 TE VEL DL

(Ref. 20601135)

Drilling metals, plastic materials and wood, with coolant  
**Usage très intensif**

Guarantee:  

Photo et textes non contractuels

### Product Information:

- Slow down motion
- Electronic speed variator
- Steel cast iron frame, head and stand
- Steel column
- Machined aluminium pulleys
- Spindle fitted on bearings
- Adjustable spindle rack motion through return spring
- 24V very low voltage controls
- ON/OFF
- Switching on lamp
- Emergency Stop through mushroom stop button
- 3-point locking circuit breaker
- Detachable servo protective shield
- 24V lighting
- Electrical protection IP54
- Noise level 50 dB
- 3-position reversible vice table (with vernier), V jaws to drill tubes
- Vice fitted on guideways to center the part to drill
- Rack-driven table, graisseur de la vis sans fin
- Hot weather adaptation on request
- Can be modified to 230V three-phase on request

### Supplied with:

- Self-clamping chuck 16 mm
- Chuck shank

### Technical characteristics:

- Height (cm) : 185.00
- Width (cm) : 47.50
- Length (cm) : 90.00
- Net weight (Kg) : 365.00
- Power(kW) 2.2
- Power (V) 3-phase 400V
- Spindle speed (rpm) 45 - 1650
- Max. drilling capacity (mm) 40
- Morse taper MT4
- Column dia (mm) 120
- Spindle stroke (mm) 150
- Number of gears Variable
- d: spindle/column distance (mm) 300
- e: spindle/base distance (mm) 1 150
- f: spindle/table distance (mm) 50-610
- Table dimension (mm) 420 x 420
- Distance between table grooves (mm) 150
- Lighting Yes
- Servo screen Yes
- Reversible vice table Yes
- Coolant Yes
- Jaw width (mm) 130
- Jaw height (mm) 40
- Opening (mm) 150
- Automatic down motion (mm/tr) No
- Slow down motion Yes
- Semi automatic tapping No
- Cross motion table No