



## SPC 40 TC DA DL

(Ref. 20601141)

Drilling metals, plastic materials and wood, with coolant  
**Usage très intensif**

Guarantee:  

Photo et textes non contractuels

### Product Information:

Cross move table, Slow down motion, automatic down motion (3 feed rates)  
Steel cast iron frame, head and stand  
Steel column  
Machined aluminium pulleys  
Transmission through V belts with rapid adjustment of tension  
Spindle fitted on bearings  
Adjustable spindle rack motion through return spring  
2-gear motor

24V very low voltage controls :

- ON/OFF
- Switching on lamp
- Emergency Stop through mushroom stay put button
- 3-point locking circuit breaker

Detachable servo protective shield

24V lighting

Electrical protection IP54

Noise level 50 dB

Rack-driven table, graisseur de la vis sans fin

Hot weather adaptation on request

Can be modified to 230V three-phase on request

Machined aluminium pulleys

### Technical characteristics:

Height (cm) : 185.00  
Width (cm) : 47.50  
Length (cm) : 90.00  
Net weight (Kg) : 600.00  
Power(kW) 2.2  
Power (V) 3-phase 400V  
Spindle speed (rpm) 45-1650  
Max. drilling capacity (mm) 40  
Milling capacity (mm) 80  
Morse taper MT4  
Column dia (mm) 140  
Spindle stroke (mm) 150  
Number of gears 14  
d: spindle/column distance (mm) 300  
e: spindle/base distance (mm) 1 150  
f: spindle/table distance (mm) 50-610  
Table dimension (mm) 300 x 540  
Distance between table grooves (mm) 150  
Lighting Yes  
Servo screen Yes  
Reversible vice table No  
Coolant Yes  
Transversal / longitudinal stroke (mm) 300 x 410  
Automatic down motion (mm/tr) 0.06 - 0.12 - 0.25  
Slow down motion Yes  
Semi automatic tapping No  
Cross motion table Yes

Supplied with Self-clamping chuck and Chuck shank