



SPC 40 TC VEL DL T

(Ref. 20601147)

Drilling metals, plastic materials and wood, with coolant
Usage très intensif

Guarantee:  **3** 

Photo et textes non contractuels

Product Information:

- Semi automatic tapping
- Cross move table
- Electronic speed variator
- Slow down motion
- Steel cast iron frame, head and stand
- Steel column
- Machined aluminium pulleys
- Transmission through V belts with rapid adujstment of tension
- Spindle fitted on bearings
- Adjustable spindle mack motion through return spring
- 24V very low voltage controls :
 - ON/OFF
 - Switching on lamp
 - Emergency Stop through mushroom stay put button
 - 3-point locking circuit breaker
- Detachable servo protective shield
- 24V lighting
- Electrical protection IP54
- Noise level 50 dB
- Rack-driven table, graisseur de la vis sans fin

Technical characteristics:

- Height (cm) : 185.00
- Width (cm) : 47.50
- Length (cm) : 90.00
- Net weight (Kg) : 410.00
- Power(kW) 0.8 / 1.47
- Power (V) 3-phase 400V
- Spindle speed (rpm) 80 - 2030
- Max. drilling capacity (mm) 40
- Milling capacity (mm) 80
- Morse taper MT4
- Column dia (mm) 140
- Spindle stroke (mm) 150
- Number of gears 14
- d: spindle/column distance (mm) 300
- e: spindle/base distance (mm) 1 150
- f: spindle/table distance (mm) 50-610
- Table dimension (mm) 300 x 540
- Distance between table grooves (mm) 150
- Lighting Yes
- Servo screen Yes

Hot weather adaptation on request
Can be modified to 230V three-phase on request
Machined aluminium pulleys

Transversal / longitudinal stroke (mm) 300 x 410
Automatic down motion (mm/tr) No
Slow down motion Yes
Semi automatic tapping Yes
Cross motion table Yes

Supplied with Self-clamping chuck and Chuck shank